

# Material Safety Data Sheet

BARESPOT UREABOR  
EPA Reg. No. 33560-47

MSDS No. PSI-008  
Date of Preparation: Nov. 1999

## Section 1 - Chemical Product and Company Identification

**Product/Chemical Name:** BARESPOT UREABOR

**Chemical Formula:** N/A

**Emergency Contact:** 901-332-7052

**Transportation Emergency Contact:** CHEMTREC: 1-800-424-9300

**Manufacturer:** Pro-Serve, Inc., 3390 Winbrook Dr., Memphis, TN 38116, *PH.* 901-332-7052, *Fax* 901-346-7157

## Section 2 - Composition / Information on Ingredients

Ingredient Name	CAS Number	wt%
Sodium Chlorate	7775-09-9	30.0
Bromacil	314-40-09	1.5
Sodium Metaborate	7775-19-1	49.0
Inert Ingredients		19.5

Ingredient	OSHA PEL		ACGIH TLV	
Sodium Chlorate	None est.	None est.	None est.	None est.
Sodium Metaborate Tetrahydrate	None est.	None est.	0 mg/M <sup>3</sup> – Nuisance Dust	

## Section 3 - Hazards Identification

☆☆☆☆☆ **Emergency Overview** ☆☆☆☆☆

### Potential Health Effects

**DANGER:** Corrosive – causes eye and skin damage

**Carcinogenicity:** IARC, NTP, and OSHA do not list BARESPOT UREABOR as a carcinogen.

## Section 4 - First Aid Measures

**Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give Oxygen. Get immediate medical attention.

**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

**Skin Contact:** In case of contact, immediately wash skin with soap and water. Wash contaminated clothing before reuse.

**Ingestion:** If swallowed, give large quantity of milk or egg whites, or if not available, drink large quantities of water. Call poison control center and follow their directions. Get medical attention.

**Note to Physician:** Probable mucosal damage may contraindicate the use of gastric lavage

## Section 5 - Fire-Fighting Measures

**Flash Point:** None established

**Flammability Classification:** None

**Extinguishing Media:** Flood with water. Sodium chlorate will decompose at 570° and supply oxygen to the fire. Smothering type extinguishers are not effective.

**Unusual Fire or Explosion Hazards:** When burned, sodium chlorate gives off oxygen, which may feed the fire. Fire may also produce toxic thermal decomposition products.

**Fire-Fighting Instructions:** Evacuate downwind from fire, and approach from upwind, wearing a self-contained breathing apparatus. Do not release runoff from fire control methods to sewers or waterways.

**Fire-Fighting Equipment:** Wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.

	Health	Fire	Reactivity	Specific
<b>NFPA Hazard Rating:</b>				
Non-fire	0	0	1	N/A
Fire	2	2	1	N/A

The NFPA Rating is a recommendation by the manufacturer using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA)

## Section 6 - Accidental Release Measures

**Spill /Leak Procedures:** Shovel or sweep up. If exposed to rain, contain and prevent run-off. Do not contaminate any body of water.

**Containment:** For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.

**Regulatory Requirements:** Follow applicable OSHA regulations (29 CFR 1910.120).

## Section 7 - Handling and Storage

**Handling Requirements:** Do not get in eyes. Avoid contact with skin. Avoid contact with clothing. Wash clothing after use.

**Storage Requirements:** **Keep** container in a cool, dry place. Do not store on wood floors. Do not store or consume food, drink or tobacco in areas where they may become contaminated with this material.

## Section 8 - Exposure Controls / Personal Protection

**Ventilation:** Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

**Respiratory Protection:** Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear an MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or non-routine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. **Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.** If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

**Protective Clothing/Equipment:** Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

**Safety Stations:** Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

**Contaminated Equipment:** Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

**Comments:** Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

## Section 9 - Physical and Chemical Properties

**Physical State:** Stable Solid

**Appearance and Odor:** White / gray pellets

**Odor Threshold:** N/A

**Vapor Pressure:** Negligible

**Vapor Density (Air=1):** N/A

**Formula Weight:** N/A

**Density:** 54 lb./ft.<sup>3</sup>

**Specific Gravity (H<sub>2</sub>O=1, at 4 °C):** N/A

**Particle Size:** 1/8" to 1/4"

**Water Solubility:** >2 lbs./gal. @68°F

**Other Solubilities:** N/A

**Boiling Point:** N/A

**Freezing/Melting Point:** N/A

**Viscosity:** N/A

**Refractive Index:** N/A

**Surface Tension:** N/A

**% Volatile:** N/A

**Auto Ignition Temperature:** Non-combustible

## Section 10 - Stability and Reactivity

**Stability:** BARESPOT UREABOR is stable at room temperature in closed containers under normal storage and handling conditions.

**Polymerization:** Hazardous polymerization cannot occur.

**Incompatibility:** Avoid strong acids and bases.

## Section 11- Toxicological Information

**Acute Oral Effects:** Rat, oral, LD<sub>50</sub>: 2710 mg/kg

**Acute Dermal Effects:** Rabbit, LD<sub>50</sub>: greater than 10 g./kg

**Carcinogenicity:** None of the components present in this material at concentrations equal or greater than .1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

**Eye Effects:** Material produces corneal opacity.